

DRUM HEATERS

DR 01

FLEXIBLE SILICON RUBBER HEATERS



APPLICATION - LOW TEMPERATURE VISCOUS PRODUCTS, MOLASSES, HONEY, OILS, RESINS, CHEMICALS, AND PAINTS.

CONSTRUCTION - SILICON RUBBER REINFORCED FIBREGLASS SHEET INCORPORATING AN INTEGRAL METAL EARTH SCREEN. COMPLETE WITH 1.2M SILICON RUBBER FLEX.

TEMPERATURE RANGE - 0 TO 40 °C

CATALOGUE #	DRUM SIZE	VOLTAGE	WATTAGE
HSRB 1	200 LTR	240	1000
HSRB 2	20 LTR	240	300



CLAMP-ON METAL BAND HEATERS



APPLICATION - LOW TO MEDIUM TEMPERATURE VISCOUS PRODUCTS, OILS, GREASE, ADHESIVES, RESINS, CHEMICALS, AND PAINTS.

CONSTRUCTION - ZINC PLATED METAL CASING ENCAPSULATING MICA INSULATED ELEMENT, INTEGRAL THERMOSTAT COMPLETE WITH PLUG CONNECTION.

TEMPERATURE RANGE - 0 TO 75 °C

CATALOGUE #	DRUM SIZE	VOLTAGE	WATTAGE
HCB 1	200 LTR	240	2400
HCB 2	20 LTR	240	500



BASE HEATERS

APPLICATION - LOW TO HIGH TEMPERATURE VISCOUS PRODUCTS, OILS, GREASE, ADHESIVES, RESINS, CHEMICALS, TAR AND PAINTS.

CONSTRUCTION - ROBUST CAST ALUMINIUM HOT PLATE, INCORPORATING A TUBULAR HEATING ELEMENT, INTEGRAL THERMOSTAT COMPLETE WITH PROVISION FOR FIXED MOUNTING.

TEMPERATURE RANGE - 0 TO 250 °C

HAZARDOUS AREAS

APPROVAL No. - 3124 X

CERTIFIED - Ex d IIB T3 IP65 CLASS 1 ZONE 1

CONSTRUCTION - ROBUST CAST ALUMINIUM HOT PLATE, INCORPORATING TUBULAR HEATING ELEMENT, INTEGRAL ELECTRIC'S AND THERMOSTAT HOUSING. FIXED FLOOR MOUNTING REQUIRED.

TEMPERATURE RANGE - 0 TO 110 °C



CATALOGUE #	DRUM SIZE	VOLTAGE	WATTAGE
HBD 1	200 LTR	240	2400
HBD 2	20 LTR	240	600
HBD 1-FF	200 LTR	240	2400

HELIOS™

MELBOURNE TEL: (03) 9556 0222

FAX: (03) 9556 0299

EMAIL: melbourne@helios.com.au

ADELAIDE TEL: (08) 8445 1477

FAX: (08) 8345 5297

EMAIL: adelaide@helios.com.au