

## TROLLEY RACK HEATER



APPLICATION - LOW TO MEDIUM TEMPERATURE VISCOUS PRODUCTS, FATS, RESINS, WAXES, TALLOW'S ECT THAT REQUIRE HEAT TO MAKE THEM FLOW.

CONSTRUCTION - ROBUST TROLLEY RACK CAPABLE OF LOADING, MANEUVERING AND DISPENSING 200L DRUMS. INCORPORATING TUBULAR HEATING ELEMENT, INTEGRAL ELECTRIC'S AND CONTROL.

TEMPERATURE RANGE - 0 TO 110 °C

CATALOGUE #	DRUM SIZE	VOLTAGE	WATTAGE
HDR 1	200 LTR	240	2400

## HEATING OVENS



APPLICATION - LOW TO HIGH TEMPERATURE PRODUCTS, THAT REQUIRE CURING, PROCESSING OR OVERNIGHT PREHEATING FOR IMMEDIATE PRODUCTION USE.

CONSTRUCTION - FABRICATED COLOUR BOND OR STAINLESS STEEL, INSULATED, FAN FORCED OR NATURAL CONVECTION, TUBULAR HEATING ELEMENT, INTEGRAL ELECTRIC'S AND CONTROL. TIMERS, CHART RECORDERS AND REMOTE CONTROL AVAILABLE ON REQUEST.

TEMPERATURE RANGE - 0 TO 350 °C

CATALOGUE #	200 LTR DRUM CAPACITY	VOLTAGE	WATTAGE
HDO 1	1	240/415	7.5 kW
HDO 4	4	240/415	18.0 kW
HDO 8	8	240/415	24.0 kW
HDO 16	16	240/415	36.0 kW



- \* CLEAN EFFICIENT
- \* CONTROLLABILITY
- \* COST EFFECTIVE
- \* PORTABILITY HDO 1 ONLY

### MANUFACTURING PLANTS

MELBOURNE TEL: (03) 9556 0222  
SYDNEY TEL: (02) 9638 7055

ADELAIDE TEL: (08) 8445 1477  
PERTH TEL: (08) 6278 4008

BRISBANE TEL: (07) 3341 5222  
Web: [www.helios.com.au](http://www.helios.com.au)